



TOMRA



# Sentinel II

## Optical Sorter

The Sentinel II optical sorter is designed to sort many food applications and is typically found in the tomato, peach and potato processing industry. Using the latest in illumination and detection technology, Sentinel II is a highly efficient and cost-effective sorting solution.

## Tailored Solution

Sentinel II's high resolution sensors and clear user interface allow the customer to set the sorter to reject a broad range of diseases and defects such as rot, green, sunburn, blemishes, etc... while also removing a broad range of foreign materials such as cotton stalks, corn cobs, pit, pit fragments, plastic, glass, animal matter, stones, wood, etc.

With three different sorter size offerings, the Sentinel II covers a wide capacity range of 20-200 tons/hour making it an ideal solution for seasonal and year round processors.

The combination of these elements of adaptability makes the Sentinel II a cost-effective option for processors of different types of produce and generates an attractive return on investment.

## Benefits

- Attractive return on investment
- Yield optimization
- High productivity
- High efficiency
- Controllable, consistent product quality
- Stable lighting/ sensors
- Robust and compact design
- Low maintenance cost
- Data rich user interface, with output to plant network



## Working Principle

The produce is spread uniformly onto the infeed belt and is scanned in the air by cameras on both sides. A few milliseconds later defects are rejected by intelligent finger ejectors, positioned at the end of the infeed belt, while the good produce continue their way along the production line.

## Technology

TOMRA technology meets the individual producer's needs while delivering a higher quality produce with less manual grading and downtime. Customers can choose from a range of factory configurations, for example, a double or single sided o-belt inspection system. The new pulsed LED and sensor system provides excellent sorting stability and requires low maintenance.

## Dimensions and Specifications

Model	Dimensions				Utilities	
	Width	Length	Height	Infeed elevation	Power	Air
<b>SENTINEL II 1000</b>	1000 mm (40")	2748 mm (108")	1332 mm (53")	710 mm (28")	3 ph+N 1.0 kVa	100 psi 7 bar
<b>SENTINEL II 1600</b>	1600 mm (64")	2748 mm (108")	1332 mm (53")	710 mm (28")	3 ph+N 2.0 kVa	100 psi 7 bar
<b>SENTINEL II 2000</b>	2000 mm (79")	2748 mm (108")	1332 mm (53")	710 mm (28")	3 ph+N 3.3 kVa	100 psi 7 bar

\*Information shown for reference and may change depending on the actual application.

Interested on more information? Please contact us directly.

[www.tomra.com/food](http://www.tomra.com/food)

